

MANILLE LYRE BOULONNEE GOUPILLE (HAUTE RÉSISTANCE)



CAP LEVAGE

DESCRIPTIF

Acier C45, zingué blanc

AVANTAGES

- Peut être livré avec un certificat de conformité.
- Coefficient de sécurité : 5 fois la CMU



DISPONIBLE SUR STOCK



RÉFÉRENCE	CMU	D	E		A	C	F	G	POIDS LE %
	t	mm	mm	pouces	mm	mm	mm	mm	kg
MHLG1	1	11	9,5	3/8	17	24,5	37	26	17,5
MHLG1.5	1,5	13	11,1	7/16	18	27	43	29	24
MHLG2	2	16	12,7	1/2	21	32	48	33	38
MHLG3.25	3,25	19	15,8	5/8	27	40	60	43	76
MHLG4.75	4,75	22	19,1	3/4	32	48	71	51	124
MHLG6.5	6,5	25	22,2	7/8	37	54	84	58	176
MHLG8.5	8,5	28	25	1	43	60	95	68	262
MHLG9.5	9,5	32	28	1 1/8	46	66	108	74	388
MHLG12	12	35	32	1 1/4	51	76	199	82	546
MHLG13.5	13,5	38	36	1 3/8	57	84	132	90	754