



ANNEAU DE LEVAGE FEMELLE GRADE 80

DESCRIPTIF


Conforme à la directive machine
 Acier allié, classe 80, trempé et revenu
 Peinture rouge ou blanche,
 Résistance -40°C à + 200°C



CAP LEVAGE

INFORMATIONS

- Coefficient de sécurité : 5 fois la CMU



RÉFÉRENCE	A/M	CMU	B	C	D	E	F	G	H	PAS MÉTRIQUE	POIDS
		T	mm	mm	mm	mm	mm	mm	mm	mm	kg
EL06	M6	0.2	31	51	30	14	44	11	6	1	0.15
EL08	M8	0.4	31	51	30	14	44	11	6	1,25	0.15
EL10	M10	0.7	31	51	30	14	44	11	6	1,5	0.15
EL12	M12	1	39	56	32	15	48	12	6	1,75	0.29
EL14	M14	1.2	39	56	32	15	48	12	6	2	0.29
EL16	M16	1.5	44	65	37	16	60	14	8	2	0.38
EL18	M18	2	44	65	37	16	60	14	8	2,5	0.38
EL20	M20	2.5	44	65	37	16	60	14	8	2,5	0.38
EL22	M22	3	52	79	48	21	75	16	11	2,5	0.63
EL24	M24	4	52	79	48	21	75	16	11	3	0.63
EL27	M27	5	52	79	48	21	75	16	11	3,5	0.63
EL30	M30	6	66	96	58	25	88	21	14	3,5	1.11